HDMI Splitter

1× 4

User Manual

Model:DK104

The 1×4 HDMI Splitter uses a single HDMI sources, accessing to multiple HDMI sinks. The Splitter allows one HDMI devices to be split easily to eight HDMI compatible monitors or projectors. The Splitter can also be placed at the end of a long HDMI cable to regenerate the HDMI signal.

FEATURES


HDMI TM (1.3b with 3D & 1080p)
Distributes 1 HDMI source to 4 HDMI Displays simultaneously.
Supports all the mandatory and several optional 3D formats
Supports High Definition Resolutions : 1080p @ 60HZ, 720p/1080i @ 120Hz
Supports Digital Audio Format, such as High Definition Audio support: Dolby TrueHD, and DTS-HD Master Audio

6) DC 5V Power

| SFECIFICATION. | |
|----------------------------|---|
| Name of the product | 1× 4 HDMI Splitter |
| Signal Inputs/ Output | 1 input4 outputs |
| HDMI Connector | Type A 19 pin female |
| HDMI Version | HDMI 1.4v |
| HDCP Version | HDCP 1.3 |
| HDMI Resolution | 24/50/60fs/1080p/1080i/720p/576p/576i/480p/ |
| | 480i |
| Support video color format | 24bit/deep color 30bit 36bit |
| Support audio format | DTS-HD/Dolly-true |
| | HD/LPCM7.1/DTS/Dolby-AC3/DSD |
| Max bandwidth | 225MHz |
| Max baud rate | 6.75Gps |
| Input cable distance | ≤15m HDMI AWG26 |
| Output cable distance | ≤25m AWG26 HDMI 1.4 standard cable |
| Input/output DDC Signal | 5 volts p-p (TTL) |
| Input/Output TMDS Signal | 0.5~1.5 Volts p-p |
| Max working current | 1.4A |
| Power adapter format | AC(50HZ,60HZ) 100V-240V;Output: DC5V |
| | |

SPECIFICATION:

| Input | |
|--------------------------|--|
| Operating Temperature | (- 15 to + 55 Celsius degree) |
| range | |
| Operating Humidity range | 5 to 90% RH (No Condensation) |
| Power Supply | 5V |
| Accessories with the | a) 5V power adapter b) one pc of manual |
| Machine | |



6①HDMI input port②Port③Port indicator of power input④It⑤Indicator of HDMI output⑥HI

②Power input④Indicator of HDMI input⑥HDMI output ports

(6)

Connecting and Operating :

 Connect the HDMI signal sources (such as PS3, STB etc) into HDMI input.
Connect the HDMI display device (such as HD-LCD, HD-DLP) into the HDMI output.

3) Plug the 5VDC power supply into power input port and the unit is ready to use.

Attention: Insert/ Extract cables gently.

PACKING CONTENTS

- 1) Main Unit. 4-port HDMI splitterr
- 2) 5VDC Power Supply
- 3) Operating Instructions

MAINTENANCE

Clean this unit with a soft, dry cloth. Never use alcohol, paint thinner of benzine to clean this unit.